


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		RELEASED FOR PRODUCTION.	2/1/2017	DPD	JAG
2	17-0080	-1 THRU -39 CH'D B/O INFO: ADDED DIM C.	3/31/2017	SM	JAG




ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-1	2	GAUGE PIN	STEEL	Ø.0240 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-3	2	GAUGE PIN	STEEL	Ø.0360 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-5	2	GAUGE PIN	STEEL	Ø.0432 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-7	2	GAUGE PIN	STEEL	Ø.0480 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-9	2	GAUGE PIN	STEEL	Ø.0540 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-11	2	GAUGE PIN	STEEL	Ø.0600 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-13	2	GAUGE PIN	STEEL	Ø.0800 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-15	2	GAUGE PIN	STEEL	Ø.0864 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-17	2	GAUGE PIN	STEEL	Ø.0960 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-19	2	GAUGE PIN	STEEL	Ø.1080 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-21	2	GAUGE PIN	STEEL	Ø.1200 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-23	2	GAUGE PIN	STEEL	Ø.1440 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-25	2	GAUGE PIN	STEEL	Ø.1440 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-27	2	GAUGE PIN	STEEL	Ø.1440 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-29	2	GAUGE PIN	STEEL	Ø.1600 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-31	2	GAUGE PIN	STEEL	Ø.1600 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-33	2	GAUGE PIN	STEEL	Ø.1728 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-35	2	GAUGE PIN	STEEL	Ø.1728 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-37	2	GAUGE PIN	STEEL	Ø.1920 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-39	2	GAUGE PIN	STEEL	Ø.2057 X 2, X CLASS, MINUS (MEYER GAGE) MODIFIED	2
			-41	1	LABEL	PAPER		3
		B/O	-43	20	VIAL WITH LID	CLEAR POLYPROPYLENE	Ø3/4 X 1-5/8 (L.A. CONTAINER #071600)	1
		B/O	-45	1	BOTTOM FOAM	ETHAFOAM 220, BLACK	2.05 X 6.13 X 10.63 (CASE SOLUTIONS)	4
		B/O	-47	1	TOP FOAM	ETHAFOAM 220, BLACK	1.05 X 6.13 X 10.63 (CASE SOLUTIONS)	5
		B/O	-49	1	CASE	PLASTIC	PELICAN #APP-1170-E	N/S
		B/O		1	PLACARD	ALUMINUM	RB41011	N/S

- NOTES:
1. REF: BHT-ALL-SPM TABLE 8-2
GEARS - MEASURING PINS VERSUS
HELICOPTER MODELS AND KIT
DESIGNATION LETTERS; 429.
 2. CUT OUT -41 LABELS AND PLACE IN
CORRESPONDING -43 VIAL.

DART AEROSPACE			
TITLE GEAR TEETH AND SPLINE MEASURING PINS			
DWG NO. RBT18003			REV 2
MAT'L HEAT TREAT FINISH SPEC		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ±.5° .X ± .1 SURFACES = 125/✓	
DRAWN BY:	DUERFELDT	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	
CHECKED:	CLOUGH	2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
OPPS APPR:	ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
QA APPR:	LINDSAY	USED ON MODEL	
APPROVED:	GILBERT	BELL 429	
SCALE	1:3	DATE	1/18/2017
		SHEET 1 OF 6	



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	17-0080	-3 THRU 39 CH'D B/O INFO; ADDED DIM C.	3/31/2017	SM	JAG



GAUGE PIN DIMENSIONS

PART NUMBER	ØA	B	C
-1	(Ø.0240)	1"	N/A
-3	(Ø.0360)	1"	
-5	(Ø.0432)	1"	
-7	(Ø.0480)	1"	
-9	(Ø.0540)	1"	
-11	(Ø.0600)	1"	
-13	(Ø.0800)	1"	
-15	(Ø.0864)	1"	
-17	(Ø.0960)	1"	
-19	(Ø.1080)	1"	
-21	(Ø.1200)	1"	
-23	(Ø.1440)	1/4"	
-25	(Ø.1440)	1"	
-27	(Ø.1440)	1"	.1209±.0050
-29	(Ø.1600)	1/4"	N/A
-31	(Ø.1600)	1"	
-33	(Ø.1728)	1/4"	
-35	(Ø.1728)	1"	
-37	(Ø.1920)	1"	
-39	(Ø.2057)	1"	



NOTE:

FLATTENED PIN.


DART AEROSPACE	
TITLE GEAR TEETH AND SPLINE MEASURING PINS	
DWG NO. RBT18003-1 THRU -39	REV 2
MAT'L STEEL HEAT TREAT FINISH SPEC	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .010 FRACTIONS ± 1/8 .XX ± .03 ANGLES ± 1° .X ± .1 SURFACES = 125° ✓	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: DUERFELDT	USED ON MODEL
CHECKED: CLOUGH	BELL 429
OPPS APPR: ANDERSON	
QA APPR: LINDSAY	
APPROVED: GILBERT	
SCALE 2:1	DATE 1/18/2017
SHEET 2 OF 6	

-1 THRU -39

GAUGE PIN

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS			
REV	ECR	DESCRIPTION	DATE
		INITIAL	APPROVED



<p>GEAR & SPLINE WEAR CHECK PINS .0240" DIA. 2 EACH - 1" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>	<p>GEAR & SPLINE WEAR CHECK PINS .0360" DIA. 2 EACH - 1" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>	<p>GEAR & SPLINE WEAR CHECK PINS .0432" DIA. 2 EACH - 1" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>	<p>GEAR & SPLINE WEAR CHECK PINS .0480" DIA. 2 EACH - 1" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>	<p>GEAR & SPLINE WEAR CHECK PINS .0540" DIA. 2 EACH - 1" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>	<p>GEAR & SPLINE WEAR CHECK PINS .0600" DIA. 2 EACH - 1" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>
<p>GEAR & SPLINE WEAR CHECK PINS .0800" DIA. 2 EACH - 1" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>	<p>GEAR & SPLINE WEAR CHECK PINS .0864" DIA. 2 EACH - 1" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>	<p>GEAR & SPLINE WEAR CHECK PINS .0960" DIA. 2 EACH - 1" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>	<p>GEAR & SPLINE WEAR CHECK PINS .1080" DIA. 2 EACH - 1" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>	<p>GEAR & SPLINE WEAR CHECK PINS .1200" DIA. 2 EACH - 1" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>	<p>GEAR & SPLINE WEAR CHECK PINS .1440" DIA. 2 EACH - 1 1/4" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>
<p>GEAR & SPLINE WEAR CHECK PINS .1440" DIA. 2 EACH - 1" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>	<p>GEAR & SPLINE WEAR CHECK PINS .1440" DIA. - FLTND 2 EACH - 1" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>	<p>GEAR & SPLINE WEAR CHECK PINS .1600" DIA. 2 EACH - 1 1/4" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>	<p>GEAR & SPLINE WEAR CHECK PINS .1600" DIA. 2 EACH - 1" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>	<p>GEAR & SPLINE WEAR CHECK PINS .1728" DIA. 2 EACH - 1 1/4" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>	<p>GEAR & SPLINE WEAR CHECK PINS .1728" DIA. 2 EACH - 1" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>
<p>GEAR & SPLINE WEAR CHECK PINS .1920" DIA. 2 EACH - 1" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>	<p>GEAR & SPLINE WEAR CHECK PINS .2057" DIA. 2 EACH - 1" LONG 100 S. DANBRO AVE. EUGENE, OR 97402 1-502-595-4195 sales@dartaero.com</p>				

1.25 TYP

5.0

1.25 TYP

7.5




(-41)

LABEL

TITLE GEAR TEETH AND SPLINE MEASURING PINS	
DWG NO. RBT18003-41	REV 2
MAT'L PAPER HEAT TREAT FINISH SPEC	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .010 FRACTIONS ± 1/8 .XX ± .03 ANGLES ± 1° .X ± .1 SURFACES = 125/✓	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY:	DUERFELDT
CHECKED:	CLOUGH
OPPS APPR:	ANDERSON
QA APPR:	LINDSAY
APPROVED:	GILBERT
SCALE	2:3
DATE	1/18/2017
SHEET 3 OF 6	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL





(-45)

BOTTOM FOAM

DART AEROSPACE	
TITLE: GEAR TEETH AND SPLINE MEASURING PINS	
DWG NO. RBT18003-45	REV. 2
MAT'L: ETHAFOAM 220, BLACK	
TREAT: <input type="checkbox"/> ANODIZE	
FINISH: <input type="checkbox"/> POLISH	
SPEC: <input type="checkbox"/> UNLESS OTHERWISE SPECIFIED	
DIMENSIONS ARE IN INCHES .XXX ± .010 FRACTIONS ± 1/8 .XX ± .03 ANGLES ± 1° .X ± .1 SURFACES = 125✓	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: DUERFELDT	USED ON MODEL
CHECKED: CLOUGH	BELL 429
OPPS APPR: ANDERSON	
QA APPR: LINDSAY	
APPROVED: GILBERT	
SCALE: 1:3	DATE: 1/18/2017
SHEET 4 OF 6	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.


REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED



(-47)
TOP FOAM

DART AEROSPACE	
TITLE: GEAR TEETH AND SPLINE MEASURING PINS	
DWG NO. RBT18003-47	REV. 2
MAT'L: ETHAFOAM 220, BLACK TREAT: _____ FINISH: _____ SPEC: _____	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .010 FRACTIONS ± 1/8 .XX ± .03 ANGLES ± 1° .X ± .1 SURFACES = 125° ✓	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: DUERFELDT	USED ON MODEL
CHECKED: CLOUGH	BELL 429
OPPS APPR: ANDERSON	
QA APPR: LINDSAY	
APPROVED: GILBERT	
SCALE 1:3	DATE 1/18/2017
SHEET 5 OF 6	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace.



NOTES:

REF: BHT-ALL-SPM TABLE 8-2
GEARS - MEASURING PINS VERSUS
HELICOPTER MODELS AND KIT
DISIGNATION LETTERS; 429.

Part #	UNIT QTY	Description
-1	2	GAUGE PIN Ø.0240 X 1
-3	2	GAUGE PIN Ø.0360 X 1
-5	2	GAUGE PIN Ø.0432 X 1
-7	2	GAUGE PIN Ø.0480 X 1
-9	2	GAUGE PIN Ø.0540 X 1
-11	2	GAUGE PIN Ø.0600 X 1
-13	2	GAUGE PIN Ø.0800 X 1
-15	2	GAUGE PIN Ø.0864 X 1
-17	2	GAUGE PIN Ø.0960 X 1
-19	2	GAUGE PIN Ø.1080 X 1
-21	2	GAUGE PIN Ø.1200 X 1
-23	2	GAUGE PIN Ø.1440 X 1/4
-25	2	GAUGE PIN Ø.1440 X 1
-27	2	GAUGE PIN Ø.1440 X 1 FLATTENED
-29	2	GAUGE PIN Ø.1600 X 1/4
-31	2	GAUGE PIN Ø.1600 X 1
-33	2	GAUGE PIN Ø.1728 X 1/4
-35	2	GAUGE PIN Ø.1728 X 1
-37	2	GAUGE PIN Ø.1920 X 1
-39	2	GAUGE PIN Ø.2057 X 1
-41	1	LABEL
-43	20	VIAL WITH LID
-45	1	BOTTOM FOAM
-47	1	TOP FOAM
-49	1	CASE
RB41011	1	PLACARD

DART
AEROSPACE

190 S. Danebo Ave., Eugene, OR. 97402

1-800-556-4166

e-mail: sales@dartaero.com

dartaerospace.com

TITLE		GEAR TEETH AND SPLINE MEASURING PINS	
DWG NO.	RBT18003	REV	CUSTOMER 1 OF 1
SCALE	1:3	DATE	1/18/2017
SHEET		6 OF 6	